



A CSW Industrials Company

RECTORSEAL PRODUCTS



· Lubricates and protects threads. For use with potable water (hot or cold)

Sealant

 Soft setting, slow drying and will not dry out in the can

Immediate pressurization on pipe up to 2" and 100 psi

Lead free and contains no other metals. Permits easy break out with no damage to threads

Brushable from 20 degree F to 140 degree F, For pressure up to 12,000 psi (liquids) and 2,600 psi (gases)

| Industry Listing | Size | Part# |
|-----------------------|-----------------|---------|
| | 32-OZ - Quart | 6311108 |
| NSF. | 16-OZ - Pint | 6312007 |
| | 1.75-OZ | 6312008 |
| FBE SYSTEM COMPATIBLE | 4-OZ - 1/4 Pint | 6312009 |
| LISTED | 8-OZ - 1/2 Pint | 6312010 |



RECTORSEAL Pipe Thread **Sealant with PTFE**

· PTFE enriched

• For use with potable water (hot or cold)

Lead free and contains no other metals

· Lubricates and protects threads

• Formulated for plastic and metal pipe

NOKORODE REGULAR PASTE FLUX

| Industry Listing | Size | Part# |
|---------------------|-----------------|---------|
| | 4-OZ - 1/4 Pint | 6311996 |
| NSF. | 8-OZ - 1/2 Pint | 6311997 |
| ∰• FB€ | 16-OZ - Pint | 6311998 |
| SYSTEM COMPATIBLE | | |

Size

Part#



| | 4-OZ - 1/4 Pint | 6311996 |
|------|-----------------|---------|
| NSF. | 8-OZ - 1/2 Pint | 6311997 |
| FBC | 16-OZ - Pint | 6311998 |
| ULC | 1.75-OZ | 6311999 |

| Cleans and fluxes in one operation saving time and money Clears smoothly into even the smallest sovity. | NSF.) PW, DWV, SW | 1.7-OZ | 6312071 | |
|---|----------------------|--------|---------|--|
| Flows smoothly into even the smallest cavity Multipurpose for use with 95/5, 60/40, 50/50, and 40/60 solder | | 8-OZ | 6312072 | |
| Lead free and acid free – safe to use on potable water systems Special oil base protects the solder joint against corrosive attack | | 16-OZ | 6312073 | |
| | | | | |

Industry

102920 Page 1 of 2





A CSW Industrials Company

RECTORSEAL PRODUCTS



| BETTER BUBBLE Leak Locator | Size | Part# |
|--|------|---------|
| Fast acting thick formula produces large, long | 8-OZ | 6312017 |

- Fast acting thick formula produces large, long lasting, well defined elastic bubbles that stand up under pressure and windy conditions
- May be used on surface temperatures from 20°F to 250°F
- Biodegradable & environmentally friendly.



| RECTORSEAL® EP-200 EPOXY PUTTY | Size | Part# |
|--------------------------------|------|-------|
|--------------------------------|------|-------|

2-OZ

6311110

- · Mixes like putty
- · Hardens in minutes
- Can be drilled, taped, filed, machined, sanded and painted



